



avd AUTO POWDER VACUUM LOADER SERIES



AVD series Auto Vacuum Loader is mainly used for food industry, chemical industry, plastic industry...etc for powder feeding. Design is for separating hopper & main machine. Per suction runs through air pressing implement & jetting filter. Be flashy to shake out dust and also keep good suction for Vacuum Loader. Without a doubt, it's excellent equipment to satisfy customers.

AVD 系列真空吸粉機主要用於，食品、化工、塑膠...等粉末輸送場合，把料斗與主機採分離設計，於每次吸粉完畢過程中，透過空氣蓄壓器，噴射逆洗濾清器，瞬間振落粉塵，隨時保持良好的吸粉效果。是絕對讓客戶放心的優良設備。

pulian
PARTNER FOR THE EXPERTS

pulian

TEL : 886-4-25362656 FAX : 886-4-25365174 E-mail : pulian@ms22.hinet.net www.pulian.com

Feature

- (1) Use high pressure air to jet, can be flashy to shake out dust. Also keep good suction.
- (2) By Fashionable type, Material hopper with polishing & precision and good looking for use.
- (3) Add a a controller can control in different place.
- (4) Build in 8 programs for your full choices.
- (5) Time of suction and clean filter can be adjusted anytime.
- (6) Dual filter design can filter powder to 3μ and clean by air for long-term running.

特點

- (1) 使用高壓空氣噴洗，能瞬間振落粉塵，保持良好吸粉效果。
- (2) 流線外型，拋光填料桶，美觀實用。
- (3) 增設遠端控制器，可以異地控制。
- (4) 內鍵 8 大程式豐富您的選擇。
- (5) 吸料時間與逆洗時間可隨時調整。
- (6) 雙濾心設計，可過濾至 03μ 粉末，並能清洗可長期使用。

Operation & Instruction 操作說明

Operation & Instruction

F1: Auto loading the timer can be adjusted 1 to 99 seconds. Lacking materials after 3 times will be alarmed.

F2: After cleaning sieve, auto loading 10 times. Run to cycle. Lacking materials after 3 times will be alarmed.

F3: After cleaning sieve, auto loading 3 times. Run to cycle. Lacking materials after 3 times will be alarmed.

F4: After cleaning sieve, auto loading 1 time. Run to cycle. Lacking materials after 3 times will be alarmed.

F5: Clean sieve continuously, push the button to stop.

F6: Edit the time to stop from 10 to 99 seconds, loading function as same as "F3". Lacking materials after 1 time will be alarmed.

F7: Edit the time to stop from 1 to 99 minutes, loading function as same as "F3". Lacking materials after 1 time will be alarmed.

F8: Edit the time to stop from 1 to 99 minutes, loading function as same as "F1". Lacking materials after 3 times will be alarmed.

操作說明

F1: 自動吸料，時間可調1~99秒，缺料3次警報。

F2: 先清網後，自動吸料10次，重複循環，缺料3次警報。

F3: 先清網後，自動吸料3次，重複循環，缺料3次警報。

F4: 先清網後，自動吸料1次，重複循環，缺料3次警報。

F5: 連續清網，要停止按。

F6: 增設停機時間可調10~99秒，吸料功能同F3，缺料1次警報。

F7: 增設停機時間可調1~99分，吸料功能同F3，缺料1次警報。

F8: 增設停機時間可調1~99分，吸料功能同F1，缺料3次警報。

MODEL	機 型	AVD-3	AVD-5
Power	馬力(HP)	3.5 HP 3 ϕ 200-415V	5 HP 3 ϕ 200-415V
Conveying Capacity	輸送能力(kg/hr)	150	250
Hopper Content	填料桶容量(lit)	60	60
Machine Size	主機尺寸(mm)	500x400x1090	500x400x1090
Hopper Size	填料桶尺寸(mm)	ϕ 400 x 730	ϕ 400 x 730
Machine Weight	機械重量(kg)	70	78
Suction Tube Diameter	吸料管尺寸(in)	1.5"	1.5"
Accessory	配備	Clamp Tube 管束 1.5" x 2 pcs ; 2" x 2 pcs Suction Tube 吸料棒 1.5" x 1 pcs P.V.C Pipe 膠管 1.5" 4m x 1 pcs ; 2" 4m x 1 pcs	

MODEL	機 型	AVD-7.5	AVD-10
Power	馬力(HP)	7.5 HP 3 ϕ 200-415V	10 HP 3 ϕ 200-415V
Conveying Capacity	輸送能力(kg/hr)	400	600
Hopper Content	填料桶容量(lit)	300	300
Machine Size	主機尺寸(mm)	610x500x1485	610x500x1485
Hopper Size	填料桶尺寸(mm)	ϕ 750 x 1500	ϕ 750 x 1500
Machine Weight	機械重量(kg)	92	105
Suction Tube Diameter	吸料管尺寸(in)	3"	3"
Accessory	配備	Clamp Tube 管束 3" x 2 pcs ; 4" x 2 pcs Suction Tube 吸料棒 3" x 1 pcs P.V.C Pipe 膠管 3" 4m x 1 pcs ; 4" 4m x 1 pcs	